

SPECIFICATIONS

Drive Motor

1/4 hp 1-phase 110/120 VAC 2-speed
4-poie, PSC Electric Motor

Control

On/Off Switch With Variable Speed

Voltage

115 VAC

Current

2.3 Amps (High Speed)

Sound Level

<75 DBA

Shipping Dim(W*H*D)

19.2"x15"x19.2" in

Display type

Digital

Cord

20 ft Power Cord

Airflow

Approximately 3000

Outlet

15A UL Rated GFCI Duplex Receptacle

Weight

39.7 lbs(18kg)

Loading quantity

20":378Sets/40":820Sets/40"HQ:942Sets

Warranty

1 Year - 100% parts and labor(all components)
2 Years - 100% parts only (all components)
3-7 Years - Materials and workmanship of the housing only.

Applications		Applications	Uni-p Vantix
Restoration Works	✓	Municipallties	✓
Confined Aears	✓	Mines&Shafts	✓
Constrction Sites	✓	Tunnels	✓
Crawl Space&Basement	✓	Tank Cleaning	✓
Electric,Gas,Water Utilities	✓	Telephone Crews	✓
Fire Departments	✓	Welding Booths	✓
Industrial Cleaning	✓	Storage Areas	✓
Manholes	✓	Vaul Cleaning	✓

Uni-P Vantix 3500 is by far the best heavy duty air mover in the market today. Built to circulate over 3,000 cubic feet of air per minute(CFM), while only drawing under 2.5 amps at 120 VAC while at high speed.

Uni-P Vantix 3500 designed to have a firm unit interlock for easy stacking and has a strong handle for easycarrying. Uni-P Vantix 3500 has a strong polypropylene housing to protect the unit from impact damage.

Uni-P Vantix 3500 is equipped with a circuit breaker to protect against a power surge. GFCI and the onboard duplex receptacle to protect the unit in wet or damp applications.



REPLACEMENT PARTS

- | | | |
|--------------------------|-----------------------|-------------------|
| 1. Breaker,CKT,12A | 2. Switch,On-Off-On | 3.Outlet,GFCI,15A |
| 4. Grill Intake | 5. Blade | 6. Hour Meter |
| 7. Grill Exhaust | 8. Stand Hardware Kit | 9. Motor |
| 10.Axial Air Mover Stand | | |



Unip Vantix 3500


Air & Movers

FEATURES

- ✓ Less than 2.5 amps on high speed
- ✓ Power-on indicator light
- ✓ Automatic hour meter displays site runtime
- ✓ GFCI protection promotes operator safety in wet applications
- ✓ Circuit breaker protects air mover and attached devices and prevents nuisance visits to the junction box
- ✓ Weighs 3.5 lbs less than competitive units
- ✓ Maintenance free Bearing Motor
- ✓ Units interlock for ease of stacking during storage and handling
- ✓ light weighted and portable



Ducting Options and chain up to 4 fans



Chain up to 4 fans



5 POSITIONS

Operating Position



Ultra Secure Stacking



Compact & Light Weight

OTHER FEATURES

- ✓ Comes with 2 long life maintenance free bearing motor.
- ✓ Has a switch on its control panel which can be used to control and regulate speed.
- ✓ It has a high air velocity of up to 3000 CFM. This is higher velocity than what any other competing products can offer.
- ✓ 20 ft AC cord with cord management


MOTOR



CONTROL PANEL



AIRFLOW



POWER LINE

